

FORENZA 350 RETRACTABLE PATIO AWNING



V.A.T. EXCLUDED

Arm Strength

Arms strength ranges from a wind speed of 28 kph to 49kph, depending on the size of the awning. Please see Wind resistance chart

Options

TOP Fix Brackets - see price list (phone to find out how many brackets)

Electric Motors and Controls- see price list

Roof Truss Brackets - see price list

Crank 1500mm - see price list

Crank 2000mm - see price list

Crank 2500mm - see price list

NEW : Crank Operated Pitch Control - see price list

Operated from 0 to 45 degrees using a crank handle on each arm bracket. Used up to 6000mm wide.

Cannot be used with cross over kit, see minimum widths under projection.

= See Price List

** = Cross Over Kit

x = Cannot be made

FULLY ASSEMBLED WITH ACRYLIC TEXTILE COVER

Overall Awning Width	1250	1800	2400	3000	3600	4200	4800	5350	5950	6450	7000
PROJECTION MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM	MM
1500											
Minimum width 2120mm (Cross Over 1210mm)	**	**									
2000	x										
Minimum width 2620mm (Cross Over 1460mm)		**	**	**							
2500	x										
Minimum width 3120mm (Cross Over 1710mm)		**	**	**	**						
3000	x	x									
Minimum width 3620mm (Cross Over 1960mm)			**	**	**						
3500	x	x									
Minimum width 4120mm (Cross Over 2210mm)			**	**	**	**					
Aluminium Rain Pelmets											
Fabric Rain Pelmet											

Standard White framework and arms. Available in Black at a 5% surcharge.

This system is designed for large awnings with a max. projection of 3500 mm .

The awning can be mounted on face or top fixed and is fully adjustable from 0 degrees to 80 degrees (min) recommended pitch for rain water run off is 15 degrees Control is by reduction gear box only operating handle (1200mm included in prices) or alternately by electric motor with or without automatic sun/wind control.

Notes

- 1 Electrical control - see price list
- 2 Sun/Wind control -used in conjunction with electric motor - see price list
- 3 All awnings are complete with mounting brackets for top or face fixing - please specify
- 4 A 1200 mm long gear operating handle is supplied with all gear controlled awnings.
A 1500, 2000 & 2500mm are also available.
- 5 The size you order is the overall size you will receive.

- 6 We do not recommend the application of P.V.C. coated, or Protent, Mode or Sheerweave fabrics on the folding arm awnings.
- 7 Please note cover width= overall width less 110 mm gear controlled.
Cover width = overall width less 70mm with electric control.
- 8 Valance = 200 mm deep or 250mm deep with Awnings requiring Cross Over Arn Kit (included in price)
- 9 Prices are based on Canvas Acrylic Fabrics
- 10 Please read Awning notes when placing an order.

IT IS THE AIM OF VENTOLITE AWNINGS TO CONTINUALLY IMPROVE ITS PRODUCTS, THE RIGHT TO ALTER DESIGNS OR SPECIFICATIONS IS THEREFORE RESERVED